

WIND

Wind Direction Transmitter Compact

Part number: 4.3129.00.xxx

Measuring transmitter for the measurement of the horizontal wind direction with serial output signal. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.

The instrument has a threaded pin PG 21 with 2 nuts for mounting.



Specification

Part number: 4.3129.00.xxx

Wind direction	
Measuring range	0 ... 360 °
Resolution	11.25 °
Accuracy	±5 °
Operating voltage	
Electronic	8 ... 30 V DC or 24 V AC
Heating	24 V AC/DC, max 20 W
General	
Ambient temp.	-40 ... +70 °C
Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Protection	IP 55

Versions

As per 4.3129.00.xxx, but:

Product number 4.3129.00.140

Data output analog	
Stromausgang	max. 500
Wind direction	0 ... 20 mA
Operating voltage	

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.00.141

Data output analog

Stromausgang	max. 500
Wind direction	4 ... 20 mA

Operating voltage

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.00.161

Data output analog

Wind direction	0 ... 10 V
Voltage output	min. 1000

Operating voltage

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.00.167

Data output analog

Wind direction	0 ... 2 V
Voltage output	min. 1000

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.00.173

Data output analog

Wind direction	0 ... 5 V
Voltage output	min. 1000

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.00.740

Data output analog

Stromausgang	max. 500
Wind direction	0 ... 20 mA

Operating voltage

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.00.741

Data output analog

Stromausgang	max. 500
Wind direction	4 ... 20 mA

Operating voltage

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.00.761

Data output analog

Wind direction	0 ... 10 V
Voltage output	min. 1000

Operating voltage

Electronic	> 15 V DC or 24 V AC
------------	----------------------

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.00.767

Data output analog

Wind direction	0 ... 2 V
Voltage output	min. 1000

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm

Weight	0.4 kg
--------	--------

Product number 4.3129.00.773




Data output analog

Wind direction	0 ... 5 V
Voltage output	min. 1000

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Accessories

Product	Product name	Brief description
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter. General Material Aluminium
	Traverse for Wind Transmitters Compact 4.3171.3x.000	For mounting the wind transmitter and wind direction transmitter jointly onto a mast. Material Traverse aluminium (AlMgSi0.5) Gripping clamb stainless steel General Sensor distance horizontal 0.8 m Weight 0.35 kg Fixing boring hole Ø 29 mm
	Traverse short for Wind Transmitters Compact 4.3171.4x.000	For mounting one wind transmitter or wind direction transmitter at a mast. Material Traverse aluminium (AlMgSi0.5) Gripping clamb stainless steel General Sensor distance horizontal 0.4 m Weight 0.3 kg Fixing boring hole Ø 29 mm



Holder compact
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

General

Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Fixing boring	hole Ø 32.5 mm

